



# Angel



<b>Housing</b>	Extruded aluminum profile
<b>Optics</b>	UV-stabilized opal diffuser
<b>LED Lifetime</b>	50.000 hours
<b>Mounting System</b>	Suspended
<b>Size Options</b>	600-900-1200 mm.
<b>Power Factor</b>	>95
<b>Light Source</b>	SMD LED
<b>Cabling</b>	Halogen-Free
<b>Input Voltage</b>	220-240V / 50-60 Hz
<b>IP Rating</b>	IP40
<b>Isolation Class</b>	Class I
<b>Ambient Temperature</b>	-20C°/+50C°

Order Code	W	Light Source Lm	CCT	L (mm)	Kg
01140.60.30.051	60	LED Module 6000	3000	600x82	3,0
01140.60.40.054	60	LED Module 6100	4000	600x82	3,0
01140.90.30.077	90	LED Module 9020	3000	900x82	4,5
01140.90.40.081	90	LED Module 90100	4000	900x82	4,5
01140.12.30.102	120	LED Module 12000	3000	1200x82	6,0
01140.12.40.108	120	LED Module 12200	4000	1200x82	6,0



Please visit our website for our updated information. [www.ikizleraydinlatma.com](http://www.ikizleraydinlatma.com)

